

**IN THE CLAIMS:**

Please amend the claims as follows

1. (AMENDED) An automatic library device for storing a plurality of ~~eartridge type~~ ~~cartridge~~ data storage devices, each having a casing containing ~~including~~ a high capacity data storage medium, and having a programmable memory ~~device~~ attached to said casing, said programmable memory ~~device~~ ~~storing being adapted to store data signals~~ describing said data storage device, said library device comprising:

~~a rack storage means having a plurality of receptacles for storing said plurality of said cartridge data storage devices;~~

~~an automatic selection means selector operable to select, retrieve and replace said cartridge data storage devices from said rack receptacles; and~~

~~a reader device capable of reading a data content stored on a said programmable data storage device, wherein for transducing data vis a vis the high capacity medium of the cartridge devices, said selection means is selector being configured to present a said data storage medium to selectively load one of cartridges in said reader device, said reader device being configured to read the data signals from said data storage device programmable memory of the cartridge loaded in the reader and print indications derived from said data signals onto a print media.~~

2. (AMENDED) The library device as claimed in claim 1, wherein said reader device comprises a port configured to accept said cartridge ~~type~~ data storage device, and a printer device located in said port, said printer ~~being~~ configured to print ~~the indications derived from the data signal~~ directly to a said data storage device when said data storage device is inserted in said port.

3. (AMENDED) The library device as claimed in claim 1, wherein said reader device comprises:

~~a receiver means capable of receiving data signals from a said programmable memory of a said data storage device; and~~

~~an interface means, arranged for interfacing with said a processor for communicating said data signals to an external processor device.~~

4. (AMENDED) The library device as claimed in claim 1, wherein said reader device comprises:

an interface means, arranged for interfacing with said a processor for communicating said data signals to an external processor device, such that inspection of information contained included in data read from said programmable memory device of said data storage device can be accessed on by said external processor device via said interface.

5. (AMENDED) The library device as claimed in claim 1, further comprising:

a read only memory means storing an operating system or for operating said a processor to display said data items received from said received means a receiver of the data items; and

a display device arranged to display said data items read from said programmable memory device via the receiver.

6. (AMENDED) The library device as claimed in claim 1, further comprising means a power source for emitting a supplying power signal to said data storage device, said power signal emitting means source being located in close proximity to said cartridge port, for supply of supplying power to said programmable memory device.

7. (CANCELED)

8. (AMENDED) The method as claimed in claim 7 14, wherein said step of printing includes printing said predetermined set of data items on a label of having a size and shape suitable for direct attachment to said data storage device, and applying said label to a cartridge of the data storage device.

9. (AMENDED) The method as claimed in claim 7 14, wherein said step of printing comprises printing said predetermined set of data items directly onto a cartridge of said data storage device.

10. (NEW) The method as claimed in claim 1, wherein the instrument includes a magnetic tape.

11. (NEW) The method as claimed in claim 14, wherein the storage device includes a magnetic tape.

12. (NEW) A method of obtaining information about a high-capacity data storage medium carried by a cartridge having a low capacity memory, the information being obtained without reading the high capacity data storage medium, the method comprising loading signals indicative of the information into the low capacity memory, subsequently loading the cartridge into a reader including a first transducer for the high capacity data storage medium and a second transducer for the low capacity memory, reading the signals indicative of the information stored in the low capacity memory by using the second transducer, and responding to the signals read by the second transducer indicative of the information stored in the low capacity memory by applying to the cartridge exterior human readable material commensurate with the information stored in the low capacity memory.

13. (NEW) The method as claimed in claim 12, wherein the medium includes a magnetic tape.

14. (NEW) A method of labeling a data storage device carrying a large capacity memory medium and a small capacity programmable memory positioned on the exterior of a casing of the data storage device, the programmable memory storing data signals describing information about the data storage device, the method comprising the steps of:

placing said data storage device in a port of a reader capable of reading the data signals;  
reading the data signals while the data storage device is in the port;  
polling a detector of said read data signals;

receiving said data signals;

storing said data signals in a memory of said reader; and

responding to the data signals stored in the memory of the reader by printing the

information in such a way that the printed information can be put on said data storage device.

*TX2  
ans.*